

## 固定式混凝土搅拌站(楼)

### Solutions for Stationary and Tower plants.

无论城市的绿色环保商品混凝土搅拌站(楼)或铁路,公路,水利等工程项目,斯加科保证能按客户要求设计出适合的全自动搅拌站。无论何时何地 and 每一种情况,客户定能以极少的资源得到所要求的生产量及高品质混凝土。



1个2.33立方米搅拌站  
1X2.33 cubic meter Stationary plant

No matter the projects are in railway, highway, water management and any other sectors, Shanghai S-Couvrot offers customized solutions for Stationary and Tower plants. We analyze the clients' needs for concrete production, and we will provide the best solutions for the jobs, wherever and whenever they may be.



2个3立方米塔楼式搅拌楼  
2X3 cubic meter Tower plant



2个3立方米塔楼式搅拌楼  
2X3 cubic meter Tower plant

上海斯加科机械有限公司

地址: 上海市宝山区富联一路200号 邮编: 201906

**Shanghai S-Couvrot Machinery Co., Ltd.**

Address: No. 200, First FuLian Road, BaoShan District, Shanghai, China 201906

Tel 电话: +86 21-3604 0550 \* Fax 传真: +86 21-3604 0559

Email 电邮: [contact@s-couvrot.com](mailto:contact@s-couvrot.com) \* Web 网站: [www.s-couvrot.com](http://www.s-couvrot.com)



## 固定式混凝土搅拌站(楼)技术参数 Specification for Stationary and Tower plants

	规格名称 Specification Items	单位 Unit	规格参数 Specification			
		型号名称 Model Name	HBP90	HBP120	HBP180	HBP240
1	生产能力 Output capacity	立方米/小时 m <sup>3</sup> /h	90	120	180	240
2	搅拌机型号 Mixer model		MA01500	MA02000	MA03000	MA04000
3	搅拌电机耗电量 Mixer Power Consumption	千瓦 kW	2 x 30	2 x 37	2 x 55	2 x 75
4	循环周期 Mixing Cycle	秒 s	60	60	60	60
5	搅拌机公称容量 Mixer Capacity	升 l	1500	2000	3000	4000
6	最大骨料颗粒 Max Aggregates size	毫米 mm	80	120	150	150
7	粉料贮缸容量 Silo size	吨 t	4 x 150	4 x 200	4 x 200	4 x 300
8	配料能力 Weighing Capacity	升 l	2400	3200	4800	6400
9	骨料贮缸容量 Aggregates Silo Capacity	立方米 m <sup>3</sup>	3 x 25	4 x 25	4 x 30	4 x 50
10	骨料种类 Types of Aggregates	种 Types	3	4	4	4
11	骨料皮带输送机生产率 Aggregate conveyor capacity	吨/小时 t/h	500	700	700	1200
12	螺旋输送机最大生产率 Maximum screw conveyor capacity	吨/小时 t/h	80	80	110	110
13	卸料高度 Discharge heights	米 m	4	4	4	4
14	装机耗电量 Total Power consumption	千瓦 kW	164	210	250	300
15	外型与尺寸 External Dimension	米 m	根据用户要求设计 According to design specification			
16	总重量 Total Weight	吨 t	根据实际设计情况而定 According to equipment specification			

	参数名称 Items	单位 Unit	规格参数 Specification			
		型号名称 Model Name	HBP90	HBP120	HBP180	HBP240
计量精度 Weighing Accuracy	骨料 Aggregate	公斤 kg	(0~2000) ±2%	(0~3000) ±2%	(0~3000) ±2%	(0~4000) ±2%
	水泥 Cement	公斤 kg	(0~900) ±1%	(0~1200) ±1%	(0~1800) ±1%	(0~2400) ±1%
	粉煤灰 PFA	公斤 kg	(0~500) ±1%	(0~500) ±1%	(0~500) ±1%	(0~1000) ±1%
	水 Water	公斤 kg	(0~400) ±1%	(0~600) ±1%	(0~600) ±1%	(0~900) ±1%
	外加剂 Admixture	公斤 kg	(0~30) ±1%	(0~30) ±1%	(0~50) ±1%	(0~50) ±1%

上海斯加科机械有限公司

地址: 上海市宝山区富联一路200号 邮编: 201906

Shanghai S-Couvrot Machinery Co., Ltd.

Address: No. 200, First FuLian Road, BaoShan District, Shanghai, China 201906

Tel 电话: +86 21-3604 0550 \* Fax 传真: +86 21-3604 0559

Email 电邮: contact@s-couvrot.com \* Web 网站: www.s-couvrot.com

